

# Quiz: Solidity Fundamentals

**Instructions:** 10 multiple choice questions — Select the best answer — Answers revealed after each question

## Quiz (1–5)

**Q1. What is the maximum value for uint8?**

- A) 128      B) 255      C) 256      D) 65535

## Quiz (1-5)

**Q1. What is the maximum value for uint8?**

- A) 128    B) 255    C) 256    D) 65535

**Answer: B** – uint8 is 8 bits, range 0 to  $2^8 - 1 = 255$ .

**Q2. Which address type can receive Ether?**

- A) address    B) address payable    C) bytes20    D) uint160

## Quiz (1–5)

**Q1. What is the maximum value for uint8?**

- A) 128    B) 255    C) 256    D) 65535

**Answer: B** – uint8 is 8 bits, range 0 to  $2^8 - 1 = 255$ .

**Q2. Which address type can receive Ether?**

- A) address    B) address payable    C) bytes20    D) uint160

**Answer: B** – Only address payable has transfer() and send() methods.

**Q3. What does “view” indicate about a function?**

- A) Modifies state    B) No state access    C) Reads but cannot modify    D) Internal only

## Quiz (1–5)

**Q1. What is the maximum value for uint8?**

- A) 128    B) 255    C) 256    D) 65535

**Answer: B** – uint8 is 8 bits, range 0 to  $2^8 - 1 = 255$ .

**Q2. Which address type can receive Ether?**

- A) address    B) address payable    C) bytes20    D) uint160

**Answer: B** – Only address payable has transfer() and send() methods.

**Q3. What does “view” indicate about a function?**

- A) Modifies state    B) No state access    C) Reads but cannot modify    D) Internal only

**Answer: C** – view reads state without modification, no gas when called off-chain.

**Q4. Which visibility allows ONLY internal contract calls?**

- A) public    B) external    C) internal    D) private

## Quiz (1–5)

**Q1. What is the maximum value for uint8?**

- A) 128    B) 255    C) 256    D) 65535

**Answer: B** – uint8 is 8 bits, range 0 to  $2^8 - 1 = 255$ .

**Q2. Which address type can receive Ether?**

- A) address    B) address payable    C) bytes20    D) uint160

**Answer: B** – Only address payable has transfer() and send() methods.

**Q3. What does “view” indicate about a function?**

- A) Modifies state    B) No state access    C) Reads but cannot modify    D) Internal only

**Answer: C** – view reads state without modification, no gas when called off-chain.

**Q4. Which visibility allows ONLY internal contract calls?**

- A) public    B) external    C) internal    D) private

**Answer: D** – private restricts to same contract only, not even derived contracts.

**Q5. What is the default value for uninitialized mapping entries?**

- A) null    B) undefined    C) Zero/default    D) Error

## Quiz (1–5)

**Q1. What is the maximum value for uint8?**

- A) 128    B) 255    C) 256    D) 65535

**Answer: B** – uint8 is 8 bits, range 0 to  $2^8 - 1 = 255$ .

**Q2. Which address type can receive Ether?**

- A) address    B) address payable    C) bytes20    D) uint160

**Answer: B** – Only address payable has transfer() and send() methods.

**Q3. What does “view” indicate about a function?**

- A) Modifies state    B) No state access    C) Reads but cannot modify    D) Internal only

**Answer: C** – view reads state without modification, no gas when called off-chain.

**Q4. Which visibility allows ONLY internal contract calls?**

- A) public    B) external    C) internal    D) private

**Answer: D** – private restricts to same contract only, not even derived contracts.

**Q5. What is the default value for uninitialized mapping entries?**

- A) null    B) undefined    C) Zero/default    D) Error

**Answer: C** – All keys exist with type's default (0 for uint, false for bool).

**Q6. Which error method checks invariants that should never fail?**

- A) `require()`    B) `assert()`    C) `revert()`    D) `throw`

**Q6. Which error method checks invariants that should never fail?**

A) require()    B) assert()    C) revert()    D) throw

**Answer: B** – assert() is for internal errors; failure indicates a bug.

**Q7. Which data location is cheapest for function parameters?**

A) storage    B) memory    C) calldata    D) stack

**Q6. Which error method checks invariants that should never fail?**

- A) require()    B) assert()    C) revert()    D) throw

**Answer: B** – assert() is for internal errors; failure indicates a bug.

**Q7. Which data location is cheapest for function parameters?**

- A) storage    B) memory    C) calldata    D) stack

**Answer: C** – calldata is read-only and does not copy data.

**Q8. How many event parameters can be indexed?**

- A) 1    B) 2    C) 3    D) Unlimited

**Q6. Which error method checks invariants that should never fail?**

- A) require()    B) assert()    C) revert()    D) throw

**Answer: B** – assert() is for internal errors; failure indicates a bug.

**Q7. Which data location is cheapest for function parameters?**

- A) storage    B) memory    C) calldata    D) stack

**Answer: C** – calldata is read-only and does not copy data.

**Q8. How many event parameters can be indexed?**

- A) 1    B) 2    C) 3    D) Unlimited

**Answer: C** – Up to 3 indexed parameters for efficient off-chain filtering.

**Q9. What does \_ (underscore) represent in a modifier?**

- A) Comment    B) Private prefix    C) Function body placeholder    D) Unused param

## Quiz (6–10)

**Q6. Which error method checks invariants that should never fail?**

- A) require()    B) assert()    C) revert()    D) throw

**Answer: B** – assert() is for internal errors; failure indicates a bug.

**Q7. Which data location is cheapest for function parameters?**

- A) storage    B) memory    C) calldata    D) stack

**Answer: C** – calldata is read-only and does not copy data.

**Q8. How many event parameters can be indexed?**

- A) 1    B) 2    C) 3    D) Unlimited

**Answer: C** – Up to 3 indexed parameters for efficient off-chain filtering.

**Q9. What does \_ (underscore) represent in a modifier?**

- A) Comment    B) Private prefix    C) Function body placeholder    D) Unused param

**Answer: C** – The underscore is replaced by the modified function's body.

**Q10. Which keyword is used for contract inheritance?**

- A) extends    B) implements    C) is    D) inherits

## Quiz (6–10)

**Q6. Which error method checks invariants that should never fail?**

- A) require()    B) assert()    C) revert()    D) throw

**Answer: B** – assert() is for internal errors; failure indicates a bug.

**Q7. Which data location is cheapest for function parameters?**

- A) storage    B) memory    C) calldata    D) stack

**Answer: C** – calldata is read-only and does not copy data.

**Q8. How many event parameters can be indexed?**

- A) 1    B) 2    C) 3    D) Unlimited

**Answer: C** – Up to 3 indexed parameters for efficient off-chain filtering.

**Q9. What does \_ (underscore) represent in a modifier?**

- A) Comment    B) Private prefix    C) Function body placeholder    D) Unused param

**Answer: C** – The underscore is replaced by the modified function's body.

**Q10. Which keyword is used for contract inheritance?**

- A) extends    B) implements    C) is    D) inherits

**Answer: C** – Solidity uses “is” (e.g., contract MyToken is ERC20).